

# Grout Colorant – Repair Acrylic Filler

## Safety Data Sheet

### SECTION 1: Identification

#### 1.1. Identification

Product name : Grout Colorant – Repair Acrylic Filler

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

#### 1.3. Details of the supplier of the safety data sheet

Color Fast Industries, Inc.  
912 W Hwy 67  
Alvarado, TX 76009  
T 817-546-4910

#### 1.4. Emergency telephone number

Emergency number : Chemtrec 1 800 424 9300

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Eye Irrit. 2A H319  
Carc. 2 H351  
STOT RE 2 H373

Full text of hazard classes and H-statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H319 - Causes serious eye irritation  
H351 - Suspected of causing cancer  
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P260 - Do not breathe dust/fume/gas/mist/vapors/spray  
P264 - Wash thoroughly after handling  
P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P314 - Get medical advice/attention if you feel unwell  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P405 - Store locked up  
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

# Grout Colorant – Repair Acrylic Filler

## Safety Data Sheet

### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Limestone	(CAS No) 1317-65-3	29.53	Not classified
Water	(CAS No) 7732-18-5	12	Not classified
Titanium dioxide	(CAS No) 13463-67-7	4	Carc. 2, H351
Solvent naphtha, petroleum, medium aliphatic	(CAS No) 64742-88-7	1	Not classified

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures after inhalation : Move to fresh air. If not breathing, administer artificial respiration. If breathing is difficult, qualified personnel may administer oxygen. SEEK MEDICAL ATTENTION.
- First-aid measures after skin contact : Wash thoroughly with soap and water. If irritation develops, seek medical attention.
- First-aid measures after eye contact : Immediately flush eyes with copious amounts of water for at least 15 minutes. SEEK MEDICAL ATTENTION.
- First-aid measures after ingestion : If swallowed, DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious person. SEEK MEDICAL ATTENTION.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Overexposure may result in difficulty breathing, headache, nausea, vomiting and drowsiness. Prolonged overexposure may result in lung damage.
- Symptoms/injuries after skin contact : May dry and defat skin causing cracks, irritation and dermatitis.
- Symptoms/injuries after eye contact : Severe irritation, pain and tearing marked by excess redness and swelling of the eye and possible chemical burns may result.
- Symptoms/injuries after ingestion : Can cause gastrointestinal irritation, vomiting, nausea and diarrhea.
- Aggravation of pre-existing conditions : Pre-existing eye, skin, and respiratory disorders may be aggravated by exposure to this product. Pre-existing skin or respiratory allergies may increase the chance of developing increased allergy symptoms from exposure to this product. Impaired blood forming functions from pre-existing disorders may be aggravated by exposure to this product.

### 4.3. Indication of any immediate medical attention and special treatment needed

If more than 2.0 ml per kg has been ingested and vomiting has not occurred, emesis should be induced with supervision. Keep victim's head below hips to prevent aspiration. If symptoms such as loss of gag reflex, convulsions or unconsciousness occur before emesis, gastric lavage using a cuffed endotracheal tube should be considered.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : None.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : None known.
- Explosion hazard : None known.

### 5.3. Advice for firefighters

- Protection during firefighting : Firefighters should wear full protective gear.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

No additional information available

#### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

- For containment : No special measures required.
- Methods for cleaning up : Remove all sources of ignition. Pick up and place in a suitable container for reclamation or disposal. Do not discharge into drains or sewers. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations.

# Grout Colorant – Repair Acrylic Filler

## Safety Data Sheet

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from children. Avoid contact with eyes, skin and clothing. Do not take internally. Avoid breathing vapors. Wash thoroughly after handling and before eating or drinking. Use with adequate ventilation.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep in a tightly closed container, stored in a cool, dry, well-ventilated area.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Titanium dioxide (13463-67-7)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust)
IDLH	US IDLH (mg/m <sup>3</sup> )	5000 mg/m <sup>3</sup>
Solvent naphtha, petroleum, medium aliphatic (64742-88-7)		
Not applicable		
Water (7732-18-5)		
Not applicable		
Limestone (1317-65-3)		
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable dust)

### 8.2. Exposure controls

Appropriate engineering controls : Local exhaust and general ventilation must be adequate to meet exposure standards.

Hand protection : Impermeable gloves are recommended.

Eye protection : Use safety glasses or goggles where eye contact is likely. Contact lenses should not be worn. An eye wash facility and safety shower should be placed in vicinity of product use areas.

Skin and body protection : Wear suitable working clothes.

Respiratory protection : Use NIOSH approved respirator under appropriate OSHA standards and regulations. A combination of both proper ventilation and respiratory protection would tend to eliminate most risks.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : White or colored

Odor : Slight ammonia

Odor threshold : No data available

pH : No data available

Melting point : No data available

Freezing point : No data available

Boiling point : No data available

Flash point : No data available

Relative evaporation rate (butyl acetate=1) : No data available

Flammability (solid, gas) : No data available

Explosion limits : No data available

Explosive properties : No data available

# Grout Colorant – Repair Acrylic Filler

## Safety Data Sheet

Oxidizing properties	: No data available
Vapor pressure	: No data available
Specific gravity	: 1.42
Relative vapor density at 20 °C	: No data available
Solubility	: Dispersible
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

### 9.2. Other information

Percent volatiles by volume : 2.8%

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

### 10.3. Possibility of hazardous reactions

Will not occur.

### 10.4. Conditions to avoid

Excessive heat.

### 10.5. Incompatible materials

None.

### 10.6. Hazardous decomposition products

Oxides of carbon.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>Titanium dioxide (13463-67-7)</b>	
LD50 oral rat	> 10000 mg/kg
<b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b>	
LD50 oral rat	> 25 ml/kg
LD50 dermal rabbit	> 3000 mg/kg
LC50 inhalation rat (mg/l)	> 13 mg/l/4h
ATE US (dermal)	3000 mg/kg
<b>Water (7732-18-5)</b>	
LD50 oral rat	> 90 ml/kg

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.

<b>Titanium dioxide (13463-67-7)</b>	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes
<b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b>	
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity

# Grout Colorant – Repair Acrylic Filler

## Safety Data Sheet

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : Harmful to aquatic life.

##### Solvent naphtha, petroleum, medium aliphatic (64742-88-7)

LC50 fish 1	800 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

##### Solvent naphtha, petroleum, medium aliphatic (64742-88-7)

BCF fish 1	(bioaccumulation expected)
------------	----------------------------

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

Not regulated for transport

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### Titanium dioxide (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Solvent naphtha, petroleum, medium aliphatic (64742-88-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Water (7732-18-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Limestone (1317-65-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

# Grout Colorant – Repair Acrylic Filler

## Safety Data Sheet

### 15.2. US State regulations

#### Titanium dioxide (13463-67-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

#### Titanium dioxide (13463-67-7)

U.S. - Massachusetts - Right To Know List  
U.S. - Minnesota - Hazardous Substance List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

#### Limestone (1317-65-3)

U.S. - Massachusetts - Right To Know List  
U.S. - Minnesota - Hazardous Substance List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### SECTION 16: Other information

Full text of H-phrases:

Carc. 2	Carcinogenicity Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
H319	Causes serious eye irritation
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*